



*towed spreader* **RAS**



*spreader with  
mechanical drive*



## Purpose

Towed spreader type RAS is designed for spreading salt, sand or gravel onto local roads.

## Technical description

Towed spreader type RAS features a supply roller and axle for mixing which have mechanical drive via the driving wheels of the spreader. The spreading can be turned on/off manually (standard equipment) or by the use of the control unit in the vehicle cabin (additional equipment).

Towed spreaders type RAS feature a wide radius of application since they have a capacity depending on the size of the driving vehicle's tipper box.

The leading chains (standard equipment) prevent possible contact between the driving vehicle and the spreader thus facilitating better manageability, especially in backward motion on winding roads.

type	spreader capacity [m <sup>3</sup> ]	spreader width [mm]	spreading width [mm]	weight [kg]
RAS 2400	1.2	2500	2400	650

## Standard equipment

- mixing axle;
- supply roller;
- protective grid;
- adjustable rubber apron on the front side which prevents the material leakage;
- rubber apron between the vehicle and the spreader;
- supporting wheel;
- towing hook;
- leading chains;
- mechanism for manual turning on/off of the spreading process;



## Additional equipment

- electrical mechanism for turning on/off;
- support wedges for the wheels with brackets;



*towed spreader*

- Kolodvorska 120 b, HR-48361 Kalinovac, Croatia
- tel: +385 (48) 883 112; fax: +385 (48) 280 146
- e-mail: [rasco@rasco.hr](mailto:rasco@rasco.hr)
- [www.rasco.hr](http://www.rasco.hr)



Dealer

